

Led Wall Light 57

The LED Wall Light 57 is a versatile wall mounted adjustable fitting. Adjustable head 240 degree (30 degree clockwise, 210 degree counter clockwise)

10W & 18W options for varied applications.

It adopts SMD led chip with special lens which make a comfortable visual experience.

Wall Light 57 comes with two optical options:
Type A with tempered frosted glass and Type B with clear tempered glass



2 Lancaster Place
Electron Lane
Lanseria Corporate Estate
Lanseria
+2711(0) 4620251

genesis  ne
www.genesisonelightning.com
sales@genesisonelighting.co.za

Product Specification

LED Wall Light

Product APPLICATIONS

Suitable for private and commercial lighting applications, hotels, offices residential, hospitals, etc

Product FEATURES


Adjustable head 240 degree (30 degree clockwise, 210 degree counter clockwise).
High lumen efficiency, 100-110lm/W
Clear tempered glass and frosted tempered glass options.
IP65 IK06 high protection level.
Beam angle 90 degree.
Finished colour: Black.



WL57 A



WL57 B



TECHNICAL DATA

ELECTRICAL INFORMATION

MODEL NO.	WL203N/10xx57A	WL203N/10xx57B	WL203N/18xx57Ax	WL203N/18xx57B
WATT(W)	10w		18w	
POWER SUPPLY	Internal			
RATED INPUT VOLTAGE(V)	AC220-240V			
FREQUENCY	50 / 60 Hz			
POWER FACTOR	≥0.90			
SURGE PROTECTION	-			
DRIVER TYPE	Constant Current (CC)			
DIMMABLE	Non Dimmable			
INTELLIGENT CONTROL	-			

OPTIC INFORMATION

LED TYPE	LED 2835			
LUMINOUS FLUX (±5%)	1000-1150lm	1200-1300lm	1800-1900lm	2000-2100lm
EFFICACY (4000K, RA70)	>100 LM/W			
CORRELATED COLOR TEMPERATURE	1-CCT: 3000K/4000K/5000K/5700K			
COLOR RENDERING INDEX	Ra80			
BEAM ANGLE	90°			
	-			

DIMENSIONS & MOUNT


PRODUCT DIMENSION (MM)	203×108×80	
LUMINAIRE NETWEIGHT KG	0.85kg	0.85kg
MOUNTING OPTION	Wall Mounted	
MATERIAL	Aluminium Alloy and Polycarbonate Optical Lens	
FINISH	Powder Coating	
FINISHING COLOUR	Black RAL 9005	
IK RATING	IK06	
IP RATING	IP65	

LIFESPAN & WARRANTY

LIFETIME (HR)	>50,000Hrs (Ta=30°C@L70)		
OPERATING TEMP.(°C)	-30°C ~ 45°C		


Product INSTALLATION

Step 1




Loosen the screws with a hex wrench and open the back cover.

Step 2




Insert the AC wires from the waterproof ring into the back cover and connect wires correspondingly.

Step 3




Fix the back cover into the ceiling.

Step 4




Connect male and female plugs.

Step 5




Align the lamp body with the back cover.

Step 6



Lock the screws with a hex wrench to fix the lamp body.

Step 7



Adjust the lighting direction as needed.



Product IMAGES

